



Applicable for horizontal and vertical shaft position !

In order to avoid magnetic leakage flux and to achieve a good heat removal, non-ferrous metals should be used for installation or attachment of auxiliary components (not for drive shaft).

dimensions and specifications subjekt to change

rated torque	residual torque	field values			resistance at 20°C	operating times		axial force is inadmissible			admissible max. radial force: N			
		maximum values	rated current						max. admissible power loss		mass moment of inertia		weight	
$M_{max}$ [Nm]	$M_{res}$ [Nm]	P [W]	U [V]	$I_N$ [A]	R [Ω]	$t_{on}$ [ms]	$t_{off}$ [ms]	$P_v$ [W]	$P_v$ [W]	$P_v$ [W]	J [kgm <sup>2</sup> ]	J [kgm <sup>2</sup> ]		m [kg]
12	0,56	24	24	0,55	23	240	150	70	190	310	$5,2 \cdot 10^{-3}$	$14,0 \cdot 10^{-3}$ *	$0,25 \cdot 10^{-3}$	2,8
								150*	600*	1050 *				4,6*

\*) heat sink "R"

item	amount	parts
3	1	internal rotor
6	2	felt gasket
7	1	field coil 24-VDC
14	2	V ring gasket
15	2	ball bearing
16	-	air gap for magnetic powder slipping
40	1	slipping
60	1	brush holder assy.